

## DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No 305/2011

**DOP – S-460**

**REV.0**

1. **Unique identification code of the product-type:**  
SILICONA NEUTRA ALCOXI SYMA 460
2. **Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**  
COLOR, BATCH NUMBER: SEE PRODUCT PACKAGING
3. **Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**
  - SEALANT FOR FAÇADE FOR INTERIOR AND EXTERIOR APPLICATION (INTENDED FOR USE IN COLD CLIMATES): EN-15651-1: F – EXT – INT – CC
  - SEALANT USED FOR GLAZING APPLICATIONS (INTENDED FOR USE IN COLD CLIMATES): EN-15651-2: G-CC
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**  

Siliconas y Masillas SL  
Avda. Cruceiro da Coruña, 201  
15705 Santiago de Compostela · España
5. **Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):**  
NOT RELEVANT
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**  
SYSTEM 3; SYSTEM 3 FOR REACTION TO FIRE
7. **In case of the declaration of performance concerning a construction product covered by a harmonized standard:**  
EN 15651-1; EN 15651-2
8. **In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**  
NOT RELEVANT
9. **Declared performance.**

<b>Conditioning:</b>	Procedure B (according to ISO 8340)
<b>Substrate</b>	Glass without primer
	Aluminum without primer
	Mortar M2 without primer
	Mortar M1 with primer

## DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No 305/2011

**DOP – S-460**

**REV.0**

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	<b>Class E</b>	
Release of Chemicals	<b>No</b>	<b>See product safety data sheet</b>
<b>Water Tightness &amp; Air Tightness as determined by :</b>		
Resistance to flow	<b>≤ 3 mm</b>	<b>EN 15651-1,2</b>
Loss of volume	<b>≤ 10 %</b>	<b>EN 15651-1,2</b>
Adhesion/Cohesion at maintained extension after immersion in water	<b>No Failure</b>	<b>EN 15651-1</b>
Adhesion/Cohesion at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	<b>No Failure</b>	<b>EN 15651-1,2</b>
Adhesion/Cohesion properties after exposure to heat water and artificial light	<b>Pass Glass</b>	<b>EN 15651-2</b>
Elastic recovery	<b>≥ 70%</b>	<b>EN 15651-2</b>
Durability	<b>Pass</b>	<b>EN 15651-1,2</b>


Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**NOT RELEVANT**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Santiago de Compostela, 21/04/2014



Javier Cereijo Pazos  
Director Técnico